

Technical Specifications

Product Packaging:	Each roll is meticulously packaged in a re-usable suspension box or ultra sturdy tube. (No flat spots, no creases, no splices)		
	STD Lengths: 75', 150', 300'		
	STD Widths: 30", 48", 54", 60", 75" (+/-1/8")		
	Core Diameter; 3 inches i.d. Heavy-Duty		
	*Custom lengths and widths available on request		
Physical Properties:	Product Weight: 20 oz. per lineal yd., (13 oz. per sq. yd.)		
	Vinyl Weight: 17 oz. per lineal yd.		
	Fabric Weight: 3 oz. per lineal yd.		
	Thickness: 0.015 to 0.030 in.		
	*Depending on texture		
	Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven		
	*Depending on texture		
Breaking Strengths. lbs. force:	Machine Direction-warp:		
	*Exceeds Type II minimum of 50 lbs.		
	Cross Machine Direction-fill:		
	*Exceeds Type II minimum of 55 lbs		
Tearing Strength, Scale:	Machine Direction-warp:		
	*Exceeds Type II minimum of 25 lbs.		
	Cross Machine Direction-fill:		
	*Exceeds Type II minimum of 25 lbs.		
Cold Crack Resistance @ 20° F:	No Change		
Heat Aging (7 Days @ 158° F):	*Does not become stiff, brittle, discolored, or show loss of grain		
Specifications/Testing/ Certification:	Federal Specification: CCC-408 D, C, B, A	*Type II	*Class A
	CFFA Specification: CFFA-W-101-D	*Type II	*Class A
Fire Testing:	ASTM-E84 Tunnel Test	Class A	
	NFPA286 Corner Burn Test	Class A	
	NFPA265 Corner Burn Test	Class A	
	BS476 Part 6 & 7		
	*Meets and exceeds requirements for flame spread, smoke developments, and flashover		
Mold/Mildew/Bacterial Resistance:	ASTM-G21 Specifications:	Passed all requirements of CCCW-408-D	